

Important Notice: Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty is expressed or implied is made for the merchantability, fitness or suitability for the use of this product or otherwise extending beyond the description hereof except the obligation to replace that product for portion of shipment proved defective. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use. Liability is limited to product replacement only.



SRWA[®]
P R O D U C T S



ROCK BINDER™

LOCKS MATERIALS IN PLACE AND PROVIDES COLOR ENHANCEMENT

1 U.S. GALLON [3.78 LITERS]

SRW ROCK BINDER™

Rock Binder™ is a liquid-bonding agent that holds a variety of rocks and aggregates up to 3/4" angular stone and 3/8" round stone together. It bonds and stabilizes rocks and aggregates to reduce the effects of blow-out from heavy wind or leaf blowers, washout from heavy rain, and other environmental elements. Safe for use around children, plants, and animals. The surface remains flexible, allowing water to pass through.

COVERAGE:

Up to 150 sq. ft. per gallon (18.58 sq. m. per 3.78 liters). Coverage may vary depending on surface and application.

INSTRUCTIONS:

- Spread aggregate and lightly tamp/compact into place.
- Rinse the rock before applying SRW Rock Binder™ to remove dust. Let dry before applying SRW Rock Binder™.
- Stir SRW Rock Binder™ well before each use
- With a pressurized sprayer, spray SRW Rock Binder™ in a slow, even, saturating coat.
- **First Coat:** Spray SRW Rock Binder™ in a slow, even saturating coat.
Note – the product goes on white and dries clear
- **Wait 15 – 30 minutes** before applying the second coat, allowing the first coat to partially dry and become tacky. Typically, when the product is no longer white.
- **Second Coat:** Spray in a slow, even saturating coat.
- Let dry for 24 hours without rain, sprinklers, or extreme humidity. Dry time may vary based on the temperature.
- When using SRW Rock Binder™ for dust and erosion control, please refer to our User Tips for instructions.

CLEANUP:

Immediately rinse off all equipment with clean water and let dry.

FEATURES:

- Surface remains flexible and permeable
- Helps minimize weed growth
- Easy to apply with sprayer (*purchased separately*)
- Reaches full bond in 24 hours
- Allows surfaces to drain
- Environmentally safe, Low VOC
- Non-toxic
- Safe for kids, plants, and animals
- Reduces landscape maintenance
- Controls dust and erosion
- Interior/Exterior
- Reduces landscape maintenance

USER TIPS:

- Intended for decorative areas only
- Apply with a pressurized sprayer
- Maximum bond strength after 24 hours
- DO NOT apply if rain, or in extreme humidity is forecast within 24 hours. The area must remain dry during the curing process. (Bond time will be longer with colder temperatures and shorter with higher temperatures.)
- Avoid spraying directly onto plants or trees
- Always test in a small, discrete area before use
- Sprays on white, dries clear
- *For dust and erosion control: Dilute 1 part SRW Rock Binder with 5 parts water.*
- NOT recommended for areas with foot or vehicle traffic

APPLICATION AND CURING TEMPERATURES:

50-80° F (10-26° C)

APPLICATIONS:

Please note that the aggregates can be up to 3/4" angular or 3/8" round stone for SRW Rock Binder™ to work as desired.

- Pea Gravel
- Decomposed Granite
- Chip Stone
- Sand/Dirt
- Dust and Erosion Control

STORAGE: KEEP FROM

FREEZING. Store container in a cool dry area with lid firmly in place.

Keep out of the reach of children

Manufactured in the USA for

SRW[®]
P R O D U C T S

Princeton, MN 55371
SRWproducts.com



REORDER #
TAC RB CTN