



PAINT, TAR and RUBBER REMOVER for PAVERS

UPDATE

January 13th, 2023

Make sure that you have an up-to-date technical data sheet in hand by consulting our Web site: techniseal.com

Canada and U.S.A.: dial 1 800 465-7325

Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Concrete pavers and slabs and natural stone.
- Driveways, patios, terraces, commercial parking lots, pedestrian areas, etc..

PROPERTIES

- Removes paint, tar, rubber and chewing gum stains.
- Water-Rinsable

DESCRIPTION

Techniseal® Paint, Tar and Rubber Remover effectively dissolves paint, tar or bitumen, rubber and chewing gum on pavers, slabs, concrete and masonry.

DIRECTIONS

BEFORE YOU BEGIN

- Wear adequate protective clothing.
- **ALWAYS TEST** on a small hidden stain to ensure the results will meet your expectations.
- Surface should, ideally, be dry and warm to the touch.

APPLICATION

Cover stain generously with Remover; let work for 5 to 10 minutes. Reapply product and, using a small nylon scrub brush, scrub until stain is dissolved. Do not let dry; rinse immediately.

NOTE: This product dissolves any sealant; apply a new coat of sealant on stripped surface.

PACKAGING

Product code	Size	Units per box	Units per pallet
60100780 (121-541)	1 qt.	6	480

WARNING

For more information and advice on the proper handling, storage, and disposal of this product, please refer to the latest version of its Safety Data Sheet (SDS). This official document contains physical, ecological, and other important information pertaining to the safe usage of this product. Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

KEEP OUT OF REACH OF CHILDREN

TRANSPORT

For more information and advice on the proper handling and transportation of this product, please refer to the latest version of its Safety Data Sheet (SDS). Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

LIMITED WARRANTY

Having no control over the use of the products, Techniseal® does not guarantee finished work. Re-placement of any defective product shall be the buyer's sole remedy under this warranty. A proof of purchase will be required for any claim. Before using this product, user shall determine the suitability of the product for its intended use, and user alone assumes all risks and liability whatsoever in connection therewith. User shall test product in a small inconspicuous area (approx. 4 sq. ft.) under projected conditions of use. In the event that no test was carried out, the warranty will only apply to 4 sq. ft. This limited warranty excludes any liability for any consequential, incidental, indirect or special damages. Except for the limited warranty described above, manufacturer specifically disclaims and excludes any other express warranty, any implied warranty of merchantability of goods, and implied warranty of fitness of goods for any particular purpose.